

PRODUCT INFORMATION

CARPET SHIELD®

It is a clear, self-adhering protective film for most types of carpeting and with a special blend of polyethylene, is highly resistant to tears or punctures and won't shift once applied. Ideal during remodeling, painting and moving, it minimizes clean up and damage claims. Carpet Shield® is available in a variety of sizes, including reverse-wound.



Liquid Shield Recyclable



FEATURES

- Self-adhering film designed to protect carpeting
- Protects clients' carpeting from damage claims while building, remodeling or painting
- Ideal protection during inclement weather
- Highly resistant to tears and punctures
- Protects all types of carpeting for up to 30 days

APPLICATIONS

- Construction
- Moving
- Remodeling
- Model Homes
- Drywall
- Painting
- Parties
- Temporary Protection

The information in this document was obtained from sources which we believe reliable. The information is provided without any warranty expressed or implied regarding its correctness. We do not assume responsibility for loss, damage or expense in any way connected with the handling, storage, use or disposal of the product.

© 2020 Surface Shields, Inc. All rights reserved. Product names & attributes trademark of Surface Shields, Inc. where applicable.



PRODUCT SPECIFICATIONS

Thickness	2.5 mil nominal
Film	Low Density Polyethylene
Adhesive Type	Formulated Acrylic
Adhesion Level	17-25 oz/in
Tensile Strength	3000 psi
Temperature (Ideal)	70° F
Humidity (Ideal)	50%
Elongation MD	350% - 500%
Chemical Name	Acrylic PSA Tapes
Chemical Family	Acrylic PSA Polyethylene Film
Chemical Formula	Proprietary
Trade Name	Carpet Shield®
Material Use	Surface Protection

AVAILABLE SIZES

CS2130W	Clear	21" x 30'	12 lbs. Shelf Display
CS2450W	Clear	24" x 50'	18 lbs. Shelf Display
CS24200L	Clear	24" x 200'	6 lbs. Reverse Wound
CS24500	Clear	24" x 500'	15 lbs. Reverse Wound
CS241000	Clear	24" x 1000'	30 lbs. Reverse Wound
CS30200	Clear	30" x 200'	7.5 lbs. Reverse Wound
CSR30200	Clear	30" x 200'	7.5 lbs. Regular Wound
CS36200	Clear	36" x 200'	9 lbs. Reverse Wound
CS36250	Clear	36" x 250'	11 lbs. Reverse Wound
CS36500	Clear	36" x 500'	23 lbs. Reverse Wound
CS361000	Clear	36" x 1000'	45 lbs. Reverse Wound
CSS42600	Clear	42" x 600'	30 lbs. Reverse Wound
CS48500	Clear	48" x 500'	35 lbs. Reverse Wound

INSTRUCTIONS

To determine suitability, test Carpet Shield® on a small portion of carpet that is in a non-exposed area for at least 48 hours. Then, inspect to ensure there was no disturbance to the carpet fibers confirming appropriate performance of the product. Peel back edge of Carpet Shield and begin to unroll. Press down edge at beginning of area to be covered so Carpet Shield adheres. Continue rolling onto carpet, applying pressure and smoothing down the film while doing so. Carefully cut end with a sharp edge. When finished, fold edge of the film back against the roll to use at a later time. Removal: roll up Carpet Shield and discard.

HANDLING AND STORAGE

Do not apply to hardwood floors or other hard surfaces. Always test Carpet Shield on a small portion of carpet that is in a non-exposed area. Temporary protection for up to 30 days. Recommended for synthetic carpeting only. Apply only to dry carpet, do not use under damp conditions.

SAFETY

SDS sheets for Surface Shields products available by request. 8191.20

CUSTOMER SERVICE

8450 185th STREET
TINLEY PARK, IL 60487

P 844 4NO MESS
E customerservice@surfaceshields.com



surfaceshields.com