

FloorCare

satin



Water-based floor care product. To protect finished floors. Protects the finished floors by forming a protective layer against fine scratches and wear marks. Prevents pre-mature wear and prolongs the durability of the surface.

- Provides a protective layer
- Can be removed without sanding
- VOC compliant
- Excellent adhesion
- Easy to apply

Recommended use:

For refreshing finished wood, cork and resilient floor coverings without the expense of a full recoating or sanding.

Product data

ART.-NO.	ITEM-#			
10490	LO-MA-002	1qt.	12	840

pH

8.5

Contents

water, polymers, water-soluble solvents, nonionic surfactants, preservatives

Storage and transportation

Shelf life: 24 months in unopened containers.
Store and transport between 40°F to 75°F (5°C to 25°C). KEEP FROM FREEZING.

Information for Use

- BEFORE USING, READ AND UNDERSTAND ALL LABEL INSTRUCTIONS AND MATERIAL SAFETY DATA SHEETS.
- For technical advice call our Loba-Wakol Technical Service at 1-800.230.6456.
- Recommended conditions are 55°F-80°F/40-75%rH.
- ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY, APPEARANCE, AND DESIRED RESULTS.
- Shake material well before use.
- Do not thin. Do not add water.
- Do not apply at temperatures below 55°F (13°C). Make sure material is at room temperature. Always maintain adequate ventilation during all phases of the coating and drying process.
- Apply evenly at the recommended coverage rate. Avoid streaks, puddles, and lap marks.
- Floor must be free from wax, oils and dirt.

APPLICATION TOOL

Terry cloth
 LOBA Mop
 T-bar
 LOBA Wischwiesel

COVERAGE

Approx. 250 square feet per 1 quart bottle.

DRYING TIME

- Slightly stressable after 1 hours.
- Fully stressable after 12 hours.

MAINTENANCE PROCESS:

- Clean floor using Hardwood Floor Cleaner making sure the floor is free from, oils, waxes and dirt.
- Apply a thin coat of FloorCare satin and allow to dry.
- Allow 3 days curing before using any cleaners or maintenance products on freshly applied FloorCare satin

RECOMMENDATION FOR ENGINEERED WOOD FLOORING:

Due to the multitude of available engineered wood flooring types in combination with different finish qualities we recommend to also refer to the Care instructions of the manufacturer. Alternatively the suitability of the product can be tested on a sample area. For further questions contact the floor covering manufacturer or Loba-Wakol Technical Department.

COMPATIBILITY

When this product is used in combination with other LOBA products the technical information of these products must be followed. Refer to the Technical Data Sheets. LOBA cannot guarantee the suitability of products other than LOBA.

General guidelines

Cleaning of tools: Clean tools and equipment with water.

Cure Time: The stated drying and cure times are based on ideal conditions (68°F, 50% rH) at the recommended application rates. Insufficient ventilation, high humidity, lower temperatures, increased coat thickness can prolong the curing process considerably. Do not cover floors, replace carpets or rugs, or clean floors with a damp mop/cloth before the final curing has been reached.

Safety Precautions: Even when working with low or zero-emission products the usual safety measures must be taken. Keep away from children. Do not eat, drink, or smoke in working areas. Wear suitable safety gloves. Clean product off of hands. Change soiled clothes.

First Aid: If swallowed, do not induce vomiting. Call for medical help immediately. Never give anything by mouth to an unconscious person. If breathing is difficult or other respiratory complaints, remove to fresh air and get medical attention. In case of eye contact, immediately flush eyes for several minutes under running water. Generally, this product does not cause skin irritation. Call a physician if irritation occurs.

Special Information The information in this document and any other information or advice we provide is intended for our customers only, and all information and advice is subject to the terms and limitations in Loba-Wakol's General Terms and Conditions, including without limit its limited warranty ("Terms"). The Terms are not expanded, changed, or waived by the information in this document or by any information or advice given by Loba-Wakol. Loba-Wakol has no relationship or obligation to anyone other than the customer that originally purchases the product from Loba-Wakol.

The information in this document and any other information or advice we provide is the result of our prior experience and our knowledge of our products. Due to the wide variety of application possibilities and processing conditions, it is the customer's responsibility to test our product for suitability for its intended purpose. When in doubt, call our Technical Service for support. Technical Information is also available by visiting our website www.loba-wakol.com. You must read and understand, and have your professional installer read and understand, all information contained in our Terms and in our published specifications, technical data sheets, written directions for installation, use and maintenance, and labels on the product. If you have any questions during application or use, immediately stop the application and use and contact our Technical Service. For information about other products offered by Loba-Wakol, please check the technical information concerning those products.

General guidelines

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.