

TARKETT 996 A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
Revision Date: 04/18/2019

Version: 3.0

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: TARKETT 996 A

Intended Use of the Product

Use of the Substance/Mixture: No use is specified.

Name, Address, and Telephone of the Responsible Party

Company

Tarkett

30000 Aurora Road

Solon, Ohio 44139

Emergency Telephone Number

Emergency Number : CHEMTREC 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Skin Sens. 1 H317

Repr. 2 H361

Aquatic Acute 3 H402

Aquatic Chronic 3 H412

Full text of H-phrases: see section 16

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H361 - Suspected of damaging fertility or the unborn child (oral).
H402 - Harmful to aquatic life.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary Statements (GHS-US)

: P261 - Avoid breathing vapors, mist, or spray.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, and eye protection.
P302+P352 - IF ON SKIN: Wash with plenty of water.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US) Not available

TARKETT 996 A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier	% (w/w)
Bisphenol A-epichlorohydrin polymer	(CAS No) 25068-38-6	10 - 30
Oxirane, methyl-, polymer with oxirane, ether with 1,2-propanediol (2:1), polymer with 1,3-diisocyanatomethylbenzene, nonylphenol-blocked (Polyurethane Prepolymer)	(CAS No) 102900-03-8	10 - 30
Alkyl (C12-14) glycidyl ether	(CAS No) 68609-97-2	5 - 10
Trimethylolpropane triacrylate	(CAS No) 15625-89-5	1 - 5
Phenol, 4-nonyl-, branched	(CAS No) 84852-15-3	0.5 – 1.5
Quartz*	(CAS No) 14808-60-7	0.1 – 1.0

*This product contains a material that may be hazardous when present as an airborne dust. Since this product is in a liquid form, the material is not able to become airborne and cannot be inhaled. Thus, the hazards usually associated with this material are not applicable to this product.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Call a POISON CENTER or doctor/physician if you feel unwell. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Irritation to eyes, skin and respiratory tract. May cause an allergic skin reaction. Suspected of damaging fertility. Suspected of damaging the unborn child (oral).

Inhalation: May cause respiratory irritation.

Skin Contact: Causes skin irritation. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic skin reaction.

Eye Contact: Causes serious eye irritation. Symptoms may include: Redness, pain, swelling, itching, and burning, tearing, and blurred vision.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Suspected of damaging fertility or the unborn child (oral).

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, dry chemical, or sand.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Potentially violent decomposition can occur above 350 °C.

Explosion Hazard: Product is not explosive but if hazardous polymerization occurs can have an oxidizing effect that could lead to fire and possible explosion.

Reactivity: Hazardous polymerization can occur in contact with certain incompatible materials.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

TARKETT 996 A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Under fire conditions this material may produce hazardous carbon dioxide (CO₂), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing vapor, mist, or spray. Use only outdoors or in a well-ventilated area.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Do not take up in combustible material such as: saw dust or cellulosic material.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Use only non-sparking tools.

Reference to Other Sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: The substance will polymerize due to heating, on contact with incompatible materials, and under the influence of light. Heating may cause violent combustion or explosion producing acrid smoke. The substance may also spontaneously polymerize if it is not stabilized. Product to be handled in a closed system and under strictly controlled conditions.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained.

Storage Conditions: Store in a dry, cool, and well-ventilated place. Keep container closed when not in use. Keep in fireproof place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Amines. Fluorine. Ammonium salts.

Specific End Use(s)

No use is specified.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

Quartz (14808-60-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
USA ACGIH	ACGIH chemical category	A2 - Suspected Human Carcinogen

TARKETT 996 A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

USA OSHA	OSHA PEL (STEL) (mg/m ³)	250 mppcf/%SiO ₂ +5, 10mg/m ³ /%SiO ₂ +2
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³ (respirable dust)
USA IDLH	US IDLH (mg/m ³)	50 mg/m ³ (respirable dust)
Alberta	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate)
British Columbia	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable)
Manitoba	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
New Brunswick	OEL TWA (mg/m ³)	0.1 mg/m ³ (respirable fraction)
Newfoundland & Labrador	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
Nova Scotia	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
Nunavut	OEL TWA (mg/m ³)	0.1 mg/m ³ (respirable mass)
Northwest Territories	OEL TWA (mg/m ³)	0.1 mg/m ³ (respirable mass)
Ontario	OEL TWA (mg/m ³)	0.10 mg/m ³ (designated substances regulation-respirable)
Prince Edward Island	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
Québec	VEMP (mg/m ³)	0.1 mg/m ³ (respirable dust)
Saskatchewan	OEL TWA (mg/m ³)	0.05 mg/m ³ (respirable fraction)
Yukon	OEL TWA (mg/m ³)	300 particle/mL

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure, but are not required. Product to be handled under strictly controlled conditions. Ensure all national/local regulations are observed. Gas detectors should be used when toxic gases may be released. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits.

Personal Protective Equipment: Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Environmental Exposure Controls: Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink or smoke during use

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Paste – Viscous Liquid
Appearance	: Beige Thick liquid
Odor	: Not available
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: 32° F
Boiling Point	: > 425 °F (218 °C)
Flash Point	: > 200 °F (93 °C) (Setaflash method)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available

TARKETT 996 A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: 1.5
Solubility	: Not available
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Approximately 85,000 cps
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.
VOC Content (SCAQMD Rule 1168)	: <12 g/L (<0.1 lbs/gal)

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions are unlikely to occur under normal circumstances.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

Possibility of Hazardous Reactions: Hazardous polymerization can occur in contact with certain incompatible materials.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Amines. Fluorine. Ammonium salts.

Hazardous Decomposition Products: Under fire conditions this material may produce hazardous carbon dioxide (CO₂), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified

Carcinogenicity: Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Suspected of damaging fertility or the unborn child (oral).

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause respiratory irritation.

Symptoms/Injuries After Skin Contact: Causes skin irritation. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis.

Symptoms/Injuries After Eye Contact: Causes serious eye irritation. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Suspected of damaging fertility or the unborn child (oral).

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Bisphenol A-epichlorohydrin polymer (25068-38-6)	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
Phenol, 4-nonyl-, branched (84852-15-3)	
LD50 Oral Rat	580 mg/kg
LD50 Dermal Rabbit	2031 mg/kg
Phenol (108-95-2)	
LD50 Oral Rat	340 mg/kg

TARKETT 996 A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

LD50 Dermal Rabbit	630 mg/kg
LC50 Inhalation Rat	0.316 mg/l/4h (reported as 316 mg/m3/4h)
ATE US (gases)	700.00 ppmV/4h
Quartz (14808-60-7)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 5000 mg/kg
Trimethylolpropane triacrylate (15625-89-5)	
LD50 Dermal Rabbit	5000 mg/kg
Quartz (14808-60-7)	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.
Trimethylolpropane triacrylate (15625-89-5)	
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Bisphenol A-epichlorohydrin polymer (25068-38-6)	
LOEC (acute)	1 mg/l Daphnia magna
NOEC chronic crustacea	0.3 mg/l Daphnia magna
Phenol, 4-nonyl-, branched (84852-15-3)	
LC50 Fish 1	0.135 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	0.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	0.1351 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])

Persistence and Degradability

Bioaccumulative Potential

Phenol, 4-nonyl-, branched (84852-15-3)	
BCF Fish 1	271

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Sewage Disposal Recommendations: This material is hazardous to the aquatic environment. Keep out of sewers and waterways. Do not empty into drains; dispose of this material and its container in a safe way.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

SECTION 14: TRANSPORT INFORMATION

In Accordance with DOT Not regulated for transport

In Accordance with IMDG Not regulated for transport

In Accordance with IATA Not regulated for transport

In Accordance with TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
-------------------------------------	--

TARKETT 996 A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations


Bisphenol A-epichlorohydrin polymer (25068-38-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Phenol, 4-nonyl-, branched (84852-15-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. S - S - indicates a substance that is identified in a proposed or final Significant New Uses Rule.
SARA Section 313 - Emission Reporting	1.0 %
Alkyl (C12-14) glycidyl ether (68609-97-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
Propanol, oxybis-, dibenzoate (27138-31-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Quartz (14808-60-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Oxirane, methyl-, polymer with oxirane, ether with 1,2-propanediol (2:1), polymer with 1,3-diisocyanatomethylbenzene, nonylphenol-blocked (102900-03-8) (Polyurethane Prepolymer)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Trimethylolpropane triacrylate (15625-89-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

US State Regulations

Quartz (14808-60-7)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.

Quartz (14808-60-7)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	

Canadian Regulations

WHMIS Classification	
Class D Division 2 Subdivision A - Very toxic material causing other toxic effects	
Class D Division 2 Subdivision B - Toxic material causing other toxic effects	
	

Bisphenol A-epichlorohydrin polymer (25068-38-6)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Phenol, 4-nonyl-, branched (84852-15-3)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
	Class D Division 2 Subdivision B - Toxic material causing other toxic effects

TARKETT 996 A

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Alkyl (C12-14) glycidyl ether (68609-97-2)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Propanol, oxybis-, dibenzoate (27138-31-4)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Quartz (14808-60-7)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Oxirane, methyl-, polymer with oxirane, ether with 1,2-propanediol (2:1), polymer with 1,3-diisocyanatomethylbenzene, nonylphenol-blocked (102900-03-8) (Polyurethane Prepolymer)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects
Trimethylolpropane triacrylate (15625-89-5)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date	: 05/11/2015
Other Information	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H361	Suspected of damaging fertility or the unborn child
H402	Harmful to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Party Responsible for the Preparation of This Document

Tarkett
30000 Aurora Road
Solon, Ohio 44139

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2

TARKETT 996 B

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
Revision Date: 04/18/2019

Version: 3.0

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: TARKETT 996 B

Intended Use of the Product

Use of the Substance/Mixture: No use is specified.

Name, Address, and Telephone of the Responsible Party

Company

Tarkett

30000 Aurora Road

Solon, Ohio 44139

Emergency Telephone Number

Emergency Number : CHEMTREC 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Skin Corr. 1B H314

Eye Dam. 1 H318

Skin Sens. 1 H317

Aquatic Chronic 2 H411

Full text of H-phrases: see section 16

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H318 - Causes serious eye damage.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary Statements (GHS-US)

: P260 - Do not breathe vapors, mist, or spray.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, and eye protection.
P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing...

Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US) Not available

TARKETT 996 B

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier	% (w/w)
Fatty acids, C18-unsaturated, dimers, polymers with tall-oil fatty acids and triethylenetetramine	(CAS No) 68082-29-1	15 - 40
Propanol, oxybis-, dibenzoate	(CAS No) 27138-31-4	3 - 7
2,4,6-Tri(dimethylaminomethyl)phenol	(CAS No) 90-72-2	3 - 7
Tetraethylenepentamine	(CAS No) 112-57-2	3 - 7
Triethylenetetramine	(CAS No) 112-24-3	1 - 5
Quartz*	(CAS No) 14808-60-7	0.1 – 1.0

*This product contains a material that may be hazardous when present as an airborne dust. Since this product is in a liquid form, the material is not able to become airborne and cannot be inhaled. Thus, the hazards usually associated with this material are not applicable to this product.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Skin Contact: Immediately flush skin with plenty of water for at least 60 minutes. Take off contaminated clothing and wash it before reuse. Call a POISON CENTER or doctor/physician if you feel unwell.

Eye Contact: Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes severe skin burns and eye damage. May cause an allergic reaction in sensitive individuals.

Inhalation: May cause respiratory irritation.

Skin Contact: Contact may cause immediate severe irritation progressing quickly to chemical burns. Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic reaction in sensitive individuals.

Eye Contact: Serious damage to eyes. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Product is not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous polymerisation can occur on heating.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. Under fire conditions, hazardous fumes will be present.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Under fire conditions this material may produce hazardous carbon dioxide (CO₂), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke. Nitrogen oxides. Amines. Ammonia.

TARKETT 996 B

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not breathe vapor, mist or spray. Do not get in eyes, on skin, or on clothing. Use only outdoors or in a well-ventilated area. Do not allow product to spread into the environment.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Place absorbed material in closed containers for disposal. Clean up spills immediately and dispose of waste safely. Notify authorities if product enters sewers or public waters.

Reference to Other Sections

See Section 8, Exposure Controls and Personal Protection. See Section 13, Disposal Considerations.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Hazardous polymerization may occur if exposed to high temperature. Product to be handled in a closed system and under strictly controlled conditions.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained. Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers. Nitrogen containing compounds, ammonium compounds.

Specific End Use(s)

No use is specified.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

Quartz (14808-60-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
USA OSHA	OSHA PEL (STEL) (mg/m ³)	250 mppcf/%SiO ₂ +5, 10mg/m ³ /%SiO ₂ +2
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	0.05 mg/m ³ (respirable dust)
USA IDLH	US IDLH (mg/m ³)	50 mg/m ³ (respirable dust)
Alberta	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable particulate)
British Columbia	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable)
Manitoba	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
New Brunswick	OEL TWA (mg/m ³)	0.1 mg/m ³ (respirable fraction)
Newfoundland & Labrador	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
Nova Scotia	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)

TARKETT 996 B

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Nunavut	OEL TWA (mg/m ³)	0.1 mg/m ³ (respirable mass)
Northwest Territories	OEL TWA (mg/m ³)	0.1 mg/m ³ (respirable mass)
Ontario	OEL TWA (mg/m ³)	0.10 mg/m ³ (designated substances regulation-respirable)
Prince Edward Island	OEL TWA (mg/m ³)	0.025 mg/m ³ (respirable fraction)
Québec	VEMP (mg/m ³)	0.1 mg/m ³ (respirable dust)
Saskatchewan	OEL TWA (mg/m ³)	0.05 mg/m ³ (respirable fraction)
Yukon	OEL TWA (mg/m ³)	300 particle/mL
Triethylenetetramine (112-24-3)		
Ontario	OEL TWA (mg/m ³)	3 mg/m ³
Ontario	OEL TWA (ppm)	0.5 ppm

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure, but are not required. Product to be handled under strictly controlled conditions. Ensure all national/local regulations are observed. Gas detectors should be used when toxic gases may be released. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor or mists below the applicable workplace exposure limits.

Personal Protective Equipment: Protective goggles. Gloves. Protective clothing. Insufficient ventilation: wear respiratory protection. Face shield.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical safety goggles.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn.

Environmental Exposure Controls: Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink or smoke during use

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Thick liquid
Odor	: Amine Odor
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: ~ 350 °F (176.67 °C)
Flash Point	: > 200 °F (93.33 °C)
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available
Specific Gravity	: 1.4
Solubility	: Not available

TARKETT 996 B

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Approximately 30,000 cps
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.
VOC Content (SCAQMD Rule 1168)	: <12 g/L (<0.1 lbs/gal)

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous polymerisation can occur on heating.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers. Amines.

Hazardous Decomposition Products: Under fire conditions this material may produce hazardous carbon dioxide (CO₂), carbon monoxide (CO), various low molecular weight hydrocarbons, and smoke. Nitrogen oxides. Ammonia. Amines.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes severe skin burns and eye damage.

Serious Eye Damage/Irritation: Causes serious eye damage.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause respiratory irritation.

Symptoms/Injuries After Skin Contact: Contact may cause immediate severe irritation progressing quickly to chemical burns.

Symptoms may include: Redness, pain, swelling, itching, burning, dryness, and dermatitis. May cause an allergic reaction in sensitive individuals.

Symptoms/Injuries After Eye Contact: Serious damage to eyes. Symptoms may include: Redness, pain, swelling, itching, burning, tearing, and blurred vision.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Quartz (14808-60-7)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 5000 mg/kg
Fatty acids, C18-unsaturated, dimers, polymers with tall-oil fatty acids and triethylenetetramine (68082-29-1)	
LD50 Oral Rat	> 2000 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
Triethylenetetramine (112-24-3)	
LD50 Oral Rat	2500 mg/kg
LD50 Dermal Rabbit	550 mg/kg
2,4,6-Tri(dimethylaminomethyl)phenol (90-72-2)	
LD50 Oral Rat	1000 mg/kg
LD50 Dermal Rat	1280 mg/kg

TARKETT 996 B

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Tetraethylenepentamine (112-57-2)	
LD50 Oral Rat	2100 mg/kg
LD50 Dermal Rabbit	660 µl/kg
Quartz (14808-60-7)	
IARC Group	1
National Toxicology Program (NTP) Status	Known Human Carcinogens.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Toxic to aquatic life with long lasting effects.

Triethylenetetramine (112-24-3)	
LC50 Fish 1	570 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static])
EC50 Daphnia 1	31.1 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC 50 Fish 2	495 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
Tetraethylenepentamine (112-57-2)	
LC50 Fish 1	420 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])
EC50 Daphnia 1	24.1 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Persistence and Degradability Not available

Bioaccumulative Potential

Triethylenetetramine (112-24-3)	
BCF Fish 1	(no bioaccumulation expected)
Log Pow	-1.4
Tetraethylenepentamine (112-57-2)	
BCF Fish 1	(no bioaccumulation expected)
Log Pow	< 1

Mobility in Soil Not available

Other Adverse Effects

Not available

SECTION 13: DISPOSAL CONSIDERATIONS

Sewage Disposal Recommendations: Do not flush into surface water or sewer system.

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology – Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION


In Accordance with DOT

Proper Shipping Name : CORROSIVE LIQUIDS, N.O.S. (2,4,6-Tri(dimethylaminomethyl)phenol , Tetraethylenepentamine)
Hazard Class : 8
Identification Number : UN1760
Label Codes : 8
Packing Group : II
ERG Number : 171



Please note there is a DOT exemption per below:

Limited Quantities : Packages having a volumetric capacity of no more than 1.0L/0.3 gallons and meeting the requirements of 49 CFR 173.154(b) are exempt from many of the DOT requirements for this classification. Each package must display the following limited quantity label.



TARKETT 996 B

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

In Accordance with IMDG

Proper Shipping Name : CORROSIVE LIQUID, N.O.S. (2,4,6-Tri(dimethylaminomethyl)phenol , Tetraethylenepentamine)
Hazard Class : 8
Identification Number : UN1760
Packing Group : II
Label Codes : 8
EmS-No. (Fire) : F-A
EmS-No. (Spillage) : S-B
Marine pollutant : Marine pollutant



In Accordance with IATA

Proper Shipping Name : CORROSIVE LIQUID, N.O.S. (2,4,6-Tri(dimethylaminomethyl)phenol , Tetraethylenepentamine)
Packing Group : II
Identification Number : UN1760
Hazard Class : 8
Label Codes : 8
ERG Code (IATA) : 8L




In Accordance with TDG

Proper Shipping Name : CORROSIVE LIQUID, N.O.S. (2,4,6-Tri(dimethylaminomethyl)phenol , Tetraethylenepentamine)
Packing Group : II
Hazard Class : 8
Identification Number : UN1760
Label Codes : 8
Marine Pollutant (TDG) : Marine pollutant



Please note there is a TDG exemption per below:

Limited Quantities : Packages having a volumetric capacity of no more than 1.0L and meeting the requirements of Transportation of Dangerous Goods Part 1 Section 1.17 Limited Quantities are exempt from many of the TDG requirements for this classification. Each package must display the following limited quantity label.



SECTION 15: REGULATORY INFORMATION

US Federal Regulations

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard
Propanol, oxybis-, dibenzoate (27138-31-4)	Listed on the United States TSCA (Toxic Substances Control Act) inventory
Quartz (14808-60-7)	Listed on the United States TSCA (Toxic Substances Control Act) inventory
Fatty acids, C18-unsaturated, dimers, polymers with tall-oil fatty acids and triethylenetetramine (68082-29-1)	Listed on the United States TSCA (Toxic Substances Control Act) inventory
Triethylenetetramine (112-24-3)	Listed on the United States TSCA (Toxic Substances Control Act) inventory
2,4,6-Tri(dimethylaminomethyl)phenol (90-72-2)	Listed on the United States TSCA (Toxic Substances Control Act) inventory
Tetraethylenepentamine (112-57-2)	Listed on the United States TSCA (Toxic Substances Control Act) inventory

TARKETT 996 B



Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

US State Regulations

Quartz (14808-60-7)	
U.S. - California - Proposition 65 - Carcinogens List	WARNING: This product contains chemicals known to the State of California to cause cancer.
Quartz (14808-60-7)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	
Triethylenetetramine (112-24-3)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	
Tetraethylenepentamine (112-57-2)	
U.S. - Massachusetts - Right To Know List	
U.S. - New Jersey - Right to Know Hazardous Substance List	
U.S. - Pennsylvania - RTK (Right to Know) List	

Canadian Regulations

WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class E - Corrosive Material
	
Propanol, oxybis-, dibenzoate (27138-31-4)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
Quartz (14808-60-7)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Fatty acids, C18-unsaturated, dimers, polymers with tall-oil fatty acids and triethylenetetramine (68082-29-1)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class E - Corrosive Material
Triethylenetetramine (112-24-3)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 0.1 %	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class E - Corrosive Material
2,4,6-Tri(dimethylaminomethyl)phenol (90-72-2)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects Class E - Corrosive Material

TARKETT 996 B

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Tetraethylenepentamine (112-57-2)	
Listed on the Canadian DSL (Domestic Substances List)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
IDL Concentration 1 %	
WHMIS Classification	Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class E - Corrosive Material

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 07/23/2015
Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H411	Toxic to aquatic life with long lasting effects

Party Responsible for the Preparation of This Document

Tarkett
30000 Aurora Road
Solon, Ohio 44139

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2