

# ParkettOil



Maintenance oil based on solvents. To protect oiled floors.

- Retains the matte finish of oiled floors
- No self-polishing
- Suitable as spot treatment
- Removes wear marks

#### Recommended use:

Use on wood floors which have been treated with oxidizing oils.

## Product data

ART.-NO.	ITEM-#			
10461	LO-MA-007	1qt.	6	480

#### Contents

aliphatic hydrocarbons, modified vegetable oils, siccatives, water, cobalt-free siccatives

#### Storage and transportation

Shelf life: 36 months in unopened containers.  
Not sensitive to freezing.

## Information for Use

- BEFORE USING, READ AND UNDERSTAND ALL LABEL INSTRUCTIONS AND MATERIAL SAFETY DATA SHEETS.
- For technical advice call our Loba-Wakol Technical Service at 1-800.230.6456.
- Recommended conditions are 50°F-80°F/40-65%rH.
- ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY, APPEARANCE, AND DESIRED RESULTS.
- Shake material well before use.
- Do not thin. Do not add water.
- Do not apply at temperatures below 55°F (13°C). Make sure material is at room temperature. Always maintain adequate ventilation during all phases of the coating and drying process.
- Apply evenly at the recommended coverage rate. Avoid streaks, puddles, and lap marks.

#### APPLICATION TOOL

Lint free cotton cloth

#### COVERAGE

800-1,000 square feet per 1 quart bottle.

#### DRYING TIME

- Slightly stressable after 4-6 hours.
- Fully stressable after 12 hours.

## Information for Use

### MAINTENANCE PROCESS

#### For newly installed multi-layer flooring ,

as well as freshly oiled floors, clean the floor thoroughly to remove all dust and grit (sweeping, vacuuming) and apply an even coat of Oil using a lint-free cloth or a sponge, wiping off any excess oil; do not allow the oil to pool or puddle.

#### For existing floors with moderate wear.

clean thoroughly with LOBA Hardwood FloorCleaner, if necessary prepare the surface using a floor machine fitted with mildly abrasive pads (beige/green). Allow floor to dry completely. Apply Oil.

#### Floors with more extensive damage

may require treatment with impregnation oil. For more information about such treatment, see the LOBA floor-care instructions for oiled hardwood floors.

#### For larger areas

the product can be applied using the SprayCleaner method. Spray Oil onto the floor, and buff the entire area using a floor machine fitted with a white pad.

### COMPATIBILITY

When this product is used in combination with other LOBA products the technical information of these products must be followed. Refer to the Technical Data Sheets. LOBA cannot guarantee the suitability of products other than LOBA.

### IMPORTANT INFORMATION

#### WARNING! SELF-IGNITION:

**Store cloths, pads, and other tools contaminated with oil in closed metal container or soak in water immediately after use. Do not leave used rags on jobsite! Do not dispose of with sawdust!**

## General guidelines

**Cleaning of tools:** Clean tools with solvents such as brush cleaner.

**Cure Time:** The stated drying and cure times are based on ideal conditions (68°F, 50% rH) at the recommended application rates. Insufficient ventilation, high humidity, lower temperatures, increased coat thickness can prolong the curing process considerably. Do not cover floors, replace carpets or rugs, or clean floors with a damp mop/cloth before the final curing has been reached. Remaining excessive material will prolong curing. On some exotic woods curing time can be extended.

**Safety Precautions:** Flammable solvent vapors emerge during the drying process when working with products containing high quantities of solvents. As a result, fire, open flame, welding, smoking and so on are prohibited in the immediate vicinity of such products. Ventilate working areas and storage rooms well. Electrical equipment in workrooms and ancillary rooms must be switched off in sufficient time to ensure that they are cold when work begins. Any spark generation, including on electrical equipment, must be avoided. Keep material containers tightly closed. Solvent sensitive components, plants or animals (fish tanks) must be removed from areas at risk of exposure to solvent vapors.

**First Aid:** If swallowed, do not induce vomiting. Call for medical help immediately. Never give anything by mouth to an unconscious person. If breathing is difficult or other respiratory complaints, remove to fresh air and get medical attention. In case of eye contact, immediately flush eyes for several minutes under running water. Generally, this product does not cause skin irritation. Call a physician if irritation occurs.

**Special Information** The information in this document and any other information or advice we provide is intended for our customers only, and all information and advice is subject to the terms and limitations in Loba-Wakol's General Terms and Conditions, including without limit its limited warranty ("Terms"). The Terms are not expanded, changed, or waived by the information in this document or by any information or advice given by Loba-Wakol. Loba-Wakol has no relationship or obligation to anyone other than the customer that originally purchases the product from Loba-Wakol.

The information in this document and any other information or advice we provide is the result of our prior experience and our knowledge of our products. Due to the wide variety of application possibilities and processing conditions, it is the customer's responsibility to test our product for suitability for its intended purpose. When in doubt, call our Technical Service for support. Technical Information is also available by visiting our website [www.loba-wakol.com](http://www.loba-wakol.com). You must read and understand, and have your professional installer read and understand, all information contained in our Terms and in our published specifications, technical data sheets, written directions for installation, use and maintenance, and labels on the product. If you have any questions during application or use, immediately stop the application and use and contact our Technical Service. For information about other products offered by Loba-Wakol, please check the technical information concerning those products.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.