

LIQUIGUARDTM

GRIPCOTE ULTRA

PROTECTION WITHOUT POLLUTION

A **LIQUIGUARD** Product
protection without pollution



GripCote-Ultra is a water based, eco-bio friendly coating that has been formulated for application on tightly woven and artistic floor coverings. This includes Persian carpets, hallway runners, wool and cotton throw rugs used indoors, on patios or other covered areas. **GripCote-Ultra** will provide an effective and lasting non-slip surface on practically all common surfaces in homes and businesses. In addition to firmly anchoring the floor coverings, **GripCote-Ultra**'s water and oil resistant structure will protect the coated surface from being damaged by liquid spills. **GripCote-Ultra** replaces carpet pads, foam tapes and the like with a more effective and lasting non-slip coating that can be easily brushed or rolled on. It can also be sprayed when applied to large surface areas.

GripCote-Ultra will not be affected by most everyday liquids including alcohol, beverages, detergents and cleaners. It acts as a protective barrier against spills and will slow down the wear and tear of the protected surfaces. **GripCote-Ultra** has been enhanced with additives that prevent the growth of mold and mildew. The cured film is extremely flexible and will not change the feel of the carpet, nor will it damage flooring materials it contacts or the surface to which it has been applied.



GripCote-Ultra will provide excellent slip resistance on almost any type of substrate including wall-to-wall carpeting, ceramics, fiberglass, glass, metal, plastic, rubber, vinyl and wood. **GripCote-Ultra** will not stain or mar the surface it comes in contact with and will not leave a sticky residue on hands, clothing or the floor surface beneath it. **GripCote-Ultra** treated materials can be touched up when necessary by simply applying additional product as needed at the site of the damage or wear. One or more coats of **GripCote-Ultra** may be applied depending on the level of slip resistance desired. Depending on the type of fiber, tightness of weave and application efficiency, a gallon of **GripCote-Ultra** will cover approximately 300 plus square feet of surface area. Individual results may vary.

GripCote-Ultra is a white viscous material that will dry to a crystal clear and somewhat tacky finish. It is easy to apply using a soft bristle or foam brush or a tight nap roller. The target surface should be free of dirt, debris and oil or grease prior to application. While slip resistance is achieved with one coat, additional coats may be applied for a more 'rubbery' feel. Allow the first coat to partially dry before applying the second coat. The **GripCote-Ultra** coated object will be ready for use once the coating has dried fully. Depending upon the ambient temperature this should take 3 to 4 hours. Allow 24 hours or more for full cure before subjecting the article to heavy use. Do not apply at temperatures below 50°F. Avoid heavy buildup.

Appropriately mask off areas that need to be kept free of **GripCote-Ultra**. Wipe off overruns, spills and splatters immediately with water. Thoroughly clean hands and tools after use with soap and warm water. Observe all personal precautions as you would with any other paint or coating product.

LIQUIGUARD[®]
www.liquiguard.com info@liquiguard.com